

## ATLAS V SBIRS GEO FLIGHT 3 MISSION

A United Launch Alliance (ULA) Atlas V 401 rocket will launch the third Space Based Infrared System (SBIRS) satellite to geosynchronous transfer orbit. Liftoff will occur from Space Launch Complex-41 at Cape Canaveral Air Force Station, FL.

The Space Based Infrared System is considered one of the nation's highest priority space programs and is designed to provide global, persistent, infrared surveillance capabilities to meet 21<sup>st</sup> century demands in four national security mission areas:

### Missile Warning

Reliable, unambiguous, timely and accurate warning for theater and strategic missile launches.

### Missile Defense

Delivery of critical information supporting the effective operation of missile defense systems.

### Technical Intelligence

Ability to characterize infrared (IR) event signatures, phenomenology and threat performance data.

### Battlespace Awareness

Delivery of comprehensive IR data to help characterize battlespace conditions.

The SBIRS team is led by the Remote Sensing Systems Directorate at the U.S. Air Force Space and Missile Systems Center. Lockheed Martin is the prime contractor, with Northrop Grumman as the payload integrator. Air Force Space Command operates the SBIRS system.



Image Courtesy of Lockheed Martin



### Payload Fairing (PLF)


The SBIRS satellite is encapsulated in the 4-m (14-ft) diameter large payload fairing (LPF). The LPF is a bisector (two-piece shell) fairing consisting of aluminum skin/stringer construction with vertical split-line longerons. The vehicle's height with the LPF is approximately 194 ft.

### Centaur

The Centaur second stage is 10 ft in diameter and 41.5 ft long. Its propellant tanks are constructed of pressure-stabilized, corrosion resistant stainless steel. Centaur is a liquid hydrogen/liquid oxygen (cryogenic-) fueled vehicle. It uses a single RL10C-1 engine producing 22,900 lb of thrust. The cryogenic tanks are insulated with a combination of helium-purged insulation blankets, radiation shields, and spray-on foam insulation (SOFI). The Centaur forward adapter (CFA) provides the structural mountings for the fault-tolerant avionics system and the structural and electronic interfaces with the spacecraft.

### Booster

The Atlas V booster is 12.5 ft in diameter and 106.5 ft long. The booster's tanks are structurally stable and constructed of isogrid aluminum barrels, spun-formed aluminum domes and intertank skirts. Atlas booster propulsion is provided by the RD-180 engine system (a single engine with two thrust chambers). The RD-180 burns RP-1 (Rocket Propellant-1 or highly purified kerosene) and liquid oxygen, and delivers 860,200 lb of thrust at sea level. The Atlas V booster is controlled by the Centaur avionics system which provides guidance, flight control and vehicle sequencing functions during the booster and Centaur phases of flight.



## ATLAS V 401

The Atlas V 401 rocket has become the workhorse of the Atlas V fleet, delivering about half of all missions to date. In its more than 14 years of service, the 401 has delivered a diverse set of missions to orbit including national security, science and exploration and commercial as well as International Space Station resupply.

**First Launch:** Aug. 21, 2002

**Launches to Date:** 33

**Performance to GTO:** 4,750 kg (10,470 lb)

**Performance to LEO-Reference:** 9,800 kg (21,600 lb)




### America's Ride to Space

With more than a century of combined heritage, United Launch Alliance is the nation's most experienced and reliable launch service provider. ULA has successfully delivered more than 110 satellites to orbit that provide critical capabilities for troops in the field, aid meteorologists in tracking severe weather, enable personal device-based GPS navigation and unlock the mysteries of our solar system.

Join the conversation:



ULALaunch.com



## MISSION OVERVIEW

– 69<sup>th</sup> Atlas V Launch

– 116<sup>th</sup> ULA Launch




America's Ride to Space

# ATLAS V PRODUCTION AND LAUNCH

- 1 Denver, CO**  
— ULA Headquarters & Design  
Center Engineering
- 2 Harlingen, TX**  
— Payload Fairing, Boattail, Centaur  
Forward Adapter, Aft Stub Adapter &  
Launch Vehicle Adapter Fabrication
- 3 Decatur, AL**  
— Booster Fabrication & Final Assembly,  
Centaur Tank Fabrication & Centaur  
Final Assembly
- 4 West Palm Beach, FL**  
— RL10C-1 Engine Fabrication at  
Aerojet Rocketdyne
- 5 Khimki, Russia**  
— RD-180 Engine Fabrication at NPO  
Energomash





# MISSION PROFILE AND GROUND TRACE



- 1 Atlas Spaceflight Operations Center (ASOC)** | Launch Control Center and Mission Director's Center
- 2 Delta Operations Center** | ISA, Centaur, Boattail Vertical Integration
- 3 Spacecraft Processing Facility** | Spacecraft processing, testing and encapsulation
- 4 Vertical Integration Facility** | Launch vehicle integration and testing, spacecraft mate and integrated operations

- 1 Vertical Integration Facility (VIF)** (See inset)
- 2 Bridge Crane Hammerhead**
- 3 Bridge Crane**
- 4 Launch Vehicle**
- 5 Mobile Launch Platform (MLP)**
- 6 Centaur LO<sub>2</sub> Storage**
- 7 High Pressure Gas Storage**
- 8 Booster LO<sub>2</sub> Storage**
- 9 Pad Equipment Building (PEB)**
- 10 Pad ECS Shelter**



All Values Approximate